

# Safety Data Sheet FLEXCOLOR CQ

Safety Data Sheet dated: 3/23/2017 - version 1

Date of first edition: 3/23/2017

#### 1. Identification

# Product identifier

Mixture identification:

Trade name: FLEXCOLOR CQ

#### Recommended use and restrictions on use

Recommended use: Water-borne synthetic polymer based adhesive

Restrictions on use: N.A. **Supplier's details** 

Company: MAPEI INC. (Canada)

2900 Francis-Hughes Avenue H7L 3J5 - Laval - QC - CAN Phone: 1-450-662-1212

# **Emergency phone number**

(USA) CHEMTREC 1-800-424-9300 (Canada) CANUTEC 1-613-996-6666

#### 2. Hazard identification

#### Classification of the product

No specific hazards are encountered under normal product use.

#### **Label elements**

#### Precautionary statements:

P202 Do not handle until all safety precautions have been read and understood.

P261.B Avoid breathing dust.

P264.2 Wash skin thoroughly after handling.
P280.I Wear protective gloves and eye protection.

P501.A Dispose of contents/container in accordance with applicable regulations.

# Other hazards

None

# Ingredient(s) with unknown acute toxicity

None

This product contains crystalline silica (quartz sand). IARC has classified crystalline silica as a Group 1 carcinogen. Both IARC and NTP consider silica as a known human carcinogen. Evidence is based on the chronic and long-term exposure workers have had to respirable sized crystalline silica dust particles. Because this product is in liquid or paste form, it does not pose a dust hazard; therefore, this classification is not relevant. (Note: sanding of the hardened product may create a silica dust hazard)

This product contains titanium dioxide which IARC has classified as a Group 2B carcinogen (possibly carcinogenic to humans). Evidence is based on sufficient animal testing as a result of long-term inhalation at high concentrations of respirable amounts of titanium dioxide. Because this product is in liquid or paste form, it does not pose a dust hazard; therefore, this classification is not relevant. (Note: sanding of the hardened product may create a dust hazard)

# 3. Composition/information on ingredients

#### **Substances**

N.A.

#### **Mixtures**

Hazardous components within the meaning of WHMIS 2015 and related classification:

#### List of components

Quantity Name Ident. Numb. Classification

50-75 % Silica Sand CAS:14808-60-7 STOT RE 1, H372; Carc. 1A, H350

2.5-5 % Titanium dioxide CAS:13463-67-7 Carc. 2, H351

# 4. First-aid measures

### **Description of necessary first-aid measures**

In case of skin contact:

Date 4/24/2017 Production Name FLEXCOLOR CQ Page n. 1 of 7

Wash with plenty of water and soap.

In case of eyes contact:

Wash immediately with water.

In case of Ingestion:

Do not induce vomiting, get medical attention showing the SDS and the hazard label.

In case of Inhalation:

Remove casualty to fresh air and keep warm and at rest.

# Most important symptoms/effects, acute and delayed

N.A.

Indication of immediate medical attention and special treatment needed, if necessary

### 5. Fire-fighting measures

# Suitable and unsuitable extinguishing media

Suitable extinguishing media:

Water.

Carbon dioxide (CO2).

Unsuitable extinguishing media:

None in particular.

#### Specific hazards arising from the hazardous product

Do not inhale explosion and combustion gases.

Burning produces heavy smoke. Hazardous combustion products: N.A.

Explosive properties: N.A. Oxidizing properties: N.A.

# Special protective equipement and precautions for fire-fighters

Use suitable breathing apparatus.

Collect contaminated fire extinguishing water separately. This must not be discharged into drains.

Move undamaged containers from immediate hazard area if it can be done safely.

#### 6. Accidental release measures

#### Personal precautions, protective equipment and emergency procedures

Wear personal protection equipment.

Remove persons to safety.

See protective measures under point 7 and 8.

# Methods and material for containment and cleaning up

Suitable material for taking up: absorbing material, organic, sand

Wash with plenty of water.

# 7. Handling and storage

# Precautions for safe handling

Avoid contact with skin and eyes, inhalation of vapours and mists.

Exercise the greatest care when handling or opening the container.

Don't use empty container before they have been cleaned.

Before making transfer operations, assure that there aren't any incompatible material residuals in the containers.

Contamined clothing should be changed before entering eating areas.

Do not eat or drink while working.

See also section 8 for recommended protective equipment.

# Conditions for safe storage, including any incompatibilities

Storage temperature: N.A. Incompatible materials:

None in particular.

Instructions as regards storage premises:

Adequately ventilated premises.

# 8. Exposure controls/personal protection

### **Control parameters**

# List of components with OEL value

Component	OEL Type Country	Ceiling	Long Term mg/m3	Long Term ppm	Short Term mg/m3	Short Term ppm	Behaviour	Note
Silica Sand	ACGIH		0,025					A2 - Suspected Human Carcinogen;lung

Date 4/24/2017 Production Name FLEXCOLOR CQ Page n. 2 of 7

Titanium dioxide OSHA

ACGIH 10

A4 - Not Classifiable as a Human Carcinogen;lower respiratory tract irritation;

# **Appropriate engineering controls**

N.A.

# Individual protection measures, such as personal protective equipment (PPE)

Eye protection:

Use close fitting safety goggles, don't use eye lens.

Protection for skin:

Use clothing that provides comprehensive protection to the skin, e.g. cotton, rubber, PVC or viton.

Protection for hands:

Use protective gloves that provides comprehensive protection, e.g. P.V.C., neoprene or rubber.

15

Respiratory protection:

N.A.

# 9. Physical and chemical properties

#### Information on basic physical and chemical properties

Physical state: Liquid

Appearance and colour: Paste white

Odour: Latex like
Odour threshold: N.A.

pH: 8.30

Melting point / freezing point: N.A.
Initial boiling point and boiling range: N.A.

Flash point: >100 °C (212 °F)

Evaporation rate: N.A.

Upper/lower flammability or explosive limits: N.A.

Vapour density: N.A. Vapour pressure: N.A. Relative density: 1.77 g/cm3 Solubility in water: Insoluble

Solubility in oil: N.A.

Partition coefficient (n-octanol/water): N.A.

Auto-ignition temperature: N.A. Decomposition temperature: N.A.

Viscosity: N.A.

Explosive properties: N.A.
Oxidizing properties: N.A.
Solid/gas flammability: N.A.

# Other information

Substance groups relevant properties: N.A.

Miscibility: N.A.
Fat Solubility: N.A.
Conductivity: N.A.

# 10. Stability and reactivity

# Reactivity

Stable under normal conditions

# **Chemical stability**

Data not Available.

# Possibility of hazardous reactions

None.

# **Conditions to avoid**

Stable under normal conditions.

# **Incompatible materials**

None in particular.

# **Hazardous decomposition products**

None.

# 11. Toxicological information

# Information on toxicological effects

Date 4/24/2017 Production Name FLEXCOLOR CQ Page n. 3 of 7

#### Toxicological information of the mixture:

There is no toxicological data available on the mixture. Consider the individual concentration of each component to assess toxicological effects resulting from exposure to the mixture.

#### Toxicological information on main components of the mixture:

Silica Sand a) acute toxicity LD50 Oral Rat = 500 mg/kg

Titanium dioxide a) acute toxicity LD50 Oral Rat > 10000 mg/kg

#### If not differently specified, the information required in the regulation and listed below must be considered as N.A.

- a) acute toxicity
- b) skin corrosion/irritation
- c) serious eye damage/irritation
- d) respiratory or skin sensitisation
- e) germ cell mutagenicity
- f) carcinogenicity
- g) reproductive toxicity
- h) STOT-single exposure
- i) STOT-repeated exposure
- j) aspiration hazard

# Substance(s) listed on the IARC Monographs:

Silica Sand Group 1
Titanium dioxide Group 2B

#### Substance(s) listed as OSHA Carcinogen(s):

Silica Sand

Titanium dioxide

# Substance(s) listed as NIOSH Carcinogen(s):

Silica Sand

Titanium dioxide

### Substance(s) listed on the NTP report on Carcinogens:

Silica Sand

# 12. Ecological information

# **Ecotoxicity**

Adopt good working practices, so that the product is not released into the environment.

# List of components with eco-toxicological properties

Quantity Component Ident. Numb. Ecotox Infos

50-75 % Silica Sand CAS: 14808-60-7 a) Aquatic acute toxicity: LC50 carp > 10000,0000 mg/L 72h

# Persistence and degradability

N.A

# **Bioaccumulative potential**

N.A.

# Mobility in soil

N.A

#### Other adverse effects

N.A.

# 13. Disposal considerations

# Safe handling and methods for disposal

Recover if possible. In so doing, comply with the local and national regulations currently in force.

# 14. Transport information

# **UN** number

TDG-UN number: N/A ADR-UN number: N/A

Date 4/24/2017 Production Name FLEXCOLOR CQ Page n. 4 of 7

DOT-UN Number: N/A IATA-Un number: N/A IMDG-Un number: N/A

# UN proper shipping name

TDG-Shipping Name: N/A
ADR-Shipping Name: N/A
DOT-Proper Shipping Name: N/A
IATA-Technical name: N/A
IMDG-Technical name: N/A

# Transport hazard class(es)

TDG-Class: N/A
ADR-Class: N/A
DOT-Hazard Class: N/A
IATA-Class: N/A
IMDG-Class: N/A

#### Packing group

TDG-Packing Group: N/A ADR-Packing Group: N/A DOT Packing Group: N/A IATA-Packing group: N/A IMDG-Packing group: N/A

# **Environmental hazards**

Marine pollutant: No

Environmental Pollutant: N.A.

# Transport in bulk (according to Annex II of MARPOL 73/78 and the IBC Code)

N.A.

# Special precautions in connection with transport or conveyance

TDG:

TDG Special provisions: N/A

Department of Transportation (DOT):

DOT-Special Provision(s): N/A

DOT-Special Provision(s): N/A

DOT-Label(s): N/A
DOT-Symbol: N/A
DOT-Cargo Aircraft: N/A
DOT-Passenger Aircraft: N/A

DOT-Bulk: N/A
DOT-Non-Bulk: N/A
Road and Rail (ADR-RID):
ADR-Label: N/A

ADR-Hazard identification number: N/A

ADR-Transport category (Tunnel restriction code): N/A

Air (IATA):

IATA-Passenger Aircraft: N/A IATA-Cargo Aircraft: N/A

IATA-Label: N/A IATA-Subrisk: N/A IATA-Erg: N/A

IATA-Special Provisions: N/A

Sea (IMDG):

IMDG-Stowage Code: N/A
IMDG-Stowage Note: N/A
IMDG-Subrisk: N/A

IMDG-Special Provisions: N/A

IMDG-Page: N/A IMDG-Label: N/A IMDG-EMS: N/A IMDG-MFAG: N/A

# 15. Regulatory information

# Canada - Federal regulations

#### **DSL - Domestic Substances List**

DSL Inventory:

Date 4/24/2017 Production Name FLEXCOLOR CQ Page n. 5 of 7

# **NDSL - Non Domestic Substances List**

NDSL Inventory:

no substances listed

# **NPRI - National Pollutant Release Inventory**

Substances listed in NPRI:

no substances listed

# **USA - Federal regulations**

#### **TSCA - Toxic Substances Control Act**

TSCA inventory:

All the components are listed on the TSCA inventory

TSCA listed substances:

Silica Sand is listed in TSCA Section 8b

Titanium dioxide is listed in TSCA Section 8b

#### **SARA - Superfund Amendments and Reauthorization Act**

Section 302 - Extremely Hazardous Substances:

no substances listed

Section 304 - Hazardous substances:

no substances listed

Section 313 - Toxic chemical list:

no substances listed

# CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act

Substance(s) listed under CERCLA:

no substances listed

#### CAA - Clean Air Act

CAA listed substances:

no substances listed

#### **CWA - Clean Water Act**

CWA listed substances:

no substances listed

# **USA - State specific regulations**

# **California Proposition 65**

Substance(s) listed under California Proposition 65:

Silica Sand Listed as carcinogen
Titanium dioxide Listed as carcinogen

# Massachusetts Right to know

Substance(s) listed under Massachusetts Right to know:

Silica Sand

Titanium dioxide

# Pennsylvania Right to know

Substance(s) listed under Pennsylvania Right to know:

Silica Sand

Titanium dioxide

# New Jersey Right to know

Substance(s) listed under New Jersey Right to know:

Silica Sand

Titanium dioxide

# 16. Other information

Code	Description
H350	May cause cancer .
H351	Suspected of causing cancer .
H372	Causes damage to organs through prolonged or repeated exposure .

Safety Data Sheet dated: 3/23/2017 - version 1

Date 4/24/2017 Production Name FLEXCOLOR CQ Page n. 6 of 7

Product code: 904KA0000

Reasonable care has been taken in the preparation of this information, but the manufacturer makes no warranty of merchantability or any other warranty, expressed or implied, with respect to this information. The manufacturer makes no representations and assumes no liability for any direct, incidental or consequential damages resulting from its use. The information herein is presented in good faith and believed to be accurate as of the effective date given. It is the buyer's responsibility to ensure that its activities comply with Federal, State or provincial, and local laws.

This document was prepared by a competent person who has received appropriate training.

It is the duty of the user to ensure that this information is appropriate and complete with respect to the specific use intended.

This SDS cancels and replaces any preceding release.

# Legend to abbreviations and acronyms used in the safety data sheet:

ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road.

RID: Regulation Concerning the International Transport of Dangerous Goods by Rail.

IMDG: International Maritime Code for Dangerous Goods.

IATA: International Air Transport Association.

IATA-DGR: Dangerous Goods Regulation by the "International Air Transport Association" (IATA).

ICAO: International Civil Aviation Organization.

ICAO-TI: Technical Instructions by the "International Civil Aviation Organization" (ICAO).

GHS: Globally Harmonized System of Classification and Labeling of Chemicals.

CLP: Classification, Labeling, Packaging.

EINECS: European Inventory of Existing Commercial Chemical Substances.

INCI: International Nomenclature of Cosmetic Ingredients.

CAS: Chemical Abstracts Service (division of the American Chemical Society).

GefStoffVO: Ordinance on Hazardous Substances, Germany.

LC50: Lethal concentration, for 50 percent of test population.

LD50: Lethal dose, for 50 percent of test population.

DNEL: Derived No Effect Level.

PNEC: Predicted No Effect Concentration.

TLV: Threshold Limiting Value.

TWATLV: Threshold Limit Value for the Time Weighted Average 8 hour day. (ACGIH Standard).

STEL: Short Term Exposure limit.
STOT: Specific Target Organ Toxicity.
WGK: German Water Hazard Class.

KSt: Explosion coefficient.

Date 4/24/2017 Production Name FLEXCOLOR CQ Page n. 7 of 7